

FORESTRY LINE

TSLQ

MINI-FORESTRY MULCHER, WITH LOW PTO PROFILE

PTO 540 RPM/1"



Mini-Forestry mulcher, suitable on small tractor with Low pto position (40-43cm from the ground) equipped with fixed tooth rotor to cut grass, branches, wood and dense vegetation up to 15cm diam. Tractor power required from 50 to 90 hp.

STANDARD EQUIPMENT:

Three point linkage cat. II, Pto 540 rpm, rear hydraulic door, Stronger frame built with quality steel double chassis, and counter blades. 100 hp gear box with free wheel, rotor with Q fixed tooth pto cardan shaft gr. 6 with shear bolt clutch. The pushing frame is included as standard equipment.

Technical information							
		Cutting wide cm.	Exterior width cm.	Weight kg.	HP Tractor	Tooth nrs.	Belt nrs.
Model	Code			KG			
TSLQ 140	16514	140	167	690	50-90	27	4
TSLQ 160	16516	160	187	750	50-90	33	4
TSLQ 180	16518	180	207	820	70-90	39	4

Tools

Standard
Fixed teeth with carbide tungsten insert for strong vegetation and trees
Q Rotor - 180° reversible (2 sides)

Optional
COBRA Sharptooth 180° reversible (2 sides)
for grass and dense vegetation
recommended for DCR disc limiter rotor









Optional

DCR limiter rotor system available for all versions