



FORESTRY LINE

TFK

FORESTRY MOWERS FOR MINI-EXCAVATORS

- NO DRAIN LINE REQUIRED -



Mini-forestry mulcher for grass, shrubs, branches, and small trees, suitable on mini-excavators from 2,0 to 6,0 tons. It can be, also, installed on medium boom mowers with pressure circuit not less than 230 bar. Max. cutting diameter 10cm.

STANDARD EQUIPMENT:

Steel unpainted under plate, to build the hitch excavator bracket, Fixed tooth rotor with K carbide tooth, double frame with quality steel, transmission with nr.2 belts drive for TFK 70 and 90, TFK 50 has the gear cast iron motor fixed directly with rotor, and mechanical frontal door. TFK 50 size motors available are 12cc, 14cc or 16cc. TFK 70 and 90 motors size available are 12cc or 20cc and the frontal door is hydraulic with cylinder. Rotor is made with DCR limiter system as standard.

Technical information

| Model | Code | Cutting wide cm. | Exterior width cm. | Weight kg. | Excavator weigh ton. | Flow rate lt/min | Pressure set bar | Tooth nr. | Rotor diam. mm | Tool tip cutting mm |
|--------|--------|------------------|--------------------|------------|----------------------|------------------|------------------|-----------|----------------|---------------------|
| TFK 50 | 625050 | 50 | 68 | 220 | 2.0 - 3.0 | 20-30 | 190-200 | 21 | 200 | 360 |
| TFK 70 | 625070 | 70 | 88 | 285 | 3.5 - 5.0 | 25-35 | 230 | 27 | 200 | 360 |
| TFK 90 | 625090 | 90 | 108 | 380 | 4.0 - 6.0 | 40-50 | 230 | 31 | 200 | 360 |

Tools

Fixed Teeth recommended for cutting grass and dense vegetation
max size 10 cm. - Cod. ZPK0025
Rotor type K1



DCR rotor - limiter system



Optional

Oil flow divider 1/2"

Excavator hitch bracket

Valve Electro-hydraulic with cable into the cabin for the door cylinder control

Adjustable rear roller, for boom mowers application