



FORESTRY LINE

TFL-C

FORESTRY MULCHER FOR MIDI EXCAVATORS



9.0 - 15.0 Ton	90 - 100 lt/min	Ø max 15 cm
----------------	-----------------	-------------

Midi-forestry mulcher for cutting grass, bushes, branches, dense vegetation and small trees. Suitable on mini-excavator from 10,0 to 15,0 tons, with maximum power of 120hp, Max. cutting diameter 15cm.

STANDARD EQUIPMENT:

Steel unpainted under plate, to build the hitch excavator bracket, Cobra fixed knife with DCR limiter system on rotor, transmission with nr. 5 belts drive. Piston motor size available are 47 or 55cc. Every hydraulic motor is equipped with a special OSMA main valve with 3 Function, called 3F, By-pass (anticavitation), antischock (regulated at 300 bar) and oil flow regulation. Pre-setted at factory according to the size piston motor fitted on. Every Piston motor can be used without the drain port connection, but it must be specified at the order, if the excavator hasn't the drain line system on it. Frontal hydraulic door.

Technical information

Model	Code	Cutting wide cm.	Exterior width cm.	Weight kg.	Excavator weigh ton.	Flow rate lt/min	Pressure set bar	Tooth nr.	Rotor diam. mm	Tool tip cutting mm
TFL-C 100	650100									
		105	125	780	9.0 - 11.0	90-100	250-270	22	323	510
TFL-C 130	650130	130	155	825	12.0 - 15.0	90-100	250-270	26	323	510

Tools

COBRA Sharptooth 180° reversible (2 sides) for grass and dense vegetation
DCR rotor with disc limiter



Optional

Excavator hitch bracket	VM55 variable displacement hydr. Motor
Valve Electro-hydraulic with cable into the cabin for the door cylinder control	Foot support, for climbing excavator (spiders)