



**FORESTRY LINE**

**TFS-Q**  
**FORESTRY MULCHER**  
**FOR BIG EXCAVATORS**



20.0 - 25.0 Ton 170 - 180 lt/min Ø max 40 cm

Forestry mulcher for cutting grass, bushes, branches, dense vegetation and small trees. Suitable on mini-excavator from 20,0 to 25,0 tons, with maximum power of 180hp, Max. cutting diameter 40cm.

**STANDARD EQUIPMENT:**

Steel unpainted under plate, to build the hitch excavator bracket, Q carbide fixed TOOTH, transmission with nr. 5 belts drive. Piston motor size available are 47 or 55cc. Every hydraulic motor is equipped with a special OSMA main valve with 3 Function, called 3F, By-pass (anticavitation), antischock (regulated at 300 bar) and oil flow regulation. Pre-setted at factory according to the size piston motor fitted on. Every Piston motor can be used without the drain port connection, but it must specified at the order, if the excavator hasn't the drain line system on it. Frontal hydraulic door.

**Technical information**

Model	Code	Cutting wide cm.	Exterior width cm.	Weight kg.	Excavator weight ton.	Flow rate lt/min	Pressure set bar	Tooth nr.	Rotor diam. mm	Tool tip cutting mm
TFS-Q 130	690130									
TFS-Q 160	690160									

**Tools**

Fixed tooth with carbide insert for strong vegetation and trees Cod. Q Rotor - 180° reversible (2 sides)	
Optional: DCR rotor with steel profiles	

**Optional**

Excavator hitch bracket	VM80 variable displacement hydr. Motor
Valve Electro-hydraulic with cable into the cabin for the door cylinder control	
DCR limiter rotor system available for all versions	