



AGRICULTURAL LINE

TP/TPC

**FLAIL MOWER FOR GRASS,
BRANCHES FOR SHRUB
CUTTER ARMS**



245 - 330 Kg 	90 - 100 lt/min 	Ø max 7 - 8 cm
------------------	---------------------	--------------------

Flail mower heads to fit to Professional boom mowers, for road maintenance, watercourse banks maintenance.

STANDARD EQUIPMENT:

Steel unpainted plate to build the boom mower hitch bracket. Gear motor fitted direct with rotor for model TP, size available 38cc or 43cc. Piston motor fitted un-direct with belts for model TPC, size available 34cc or 47cc. Rotor with knives or hammers, 140mm rear adjustable roller, frontal protection with chains, rear protection with rubber.

Technical information

Model	Code	Cutting wide cm. 	Exterior width cm. 	Weight kg. 	Flow rate lt/min 	Pressure set bar
TP 120	520120	120	140	245	90-95	190-210
TPC 100	530100	105	130	275	90-100	210-230
TPC 125	530125	125	150	295	90-100	210-230
TPC 160	530160	160	180	330	90-100	210-230

Tools

	Multipurpose knives for grass and bushes. max size 3 cm. Cod. ZP 293016/D Rotor A3 - standard -		"Spatula" knives for grass and bushes max size 3 cm. Cod. ZP 137001 Rotor C - optional -
	"Spatula" Knives for grass and bushes. max size 5 cm. Cod. ZP 173001 Rotor I - optional -		

Optional

Hitch bracket for boom mowers	Hydraulic frontal door (hoses not included)
-------------------------------	---