



FORESTRY LINE

SS/TFF

**FORESTRY MULCHER
FOR BIG SKID STEER LOADER
AND BIG LOADER**

- NO DRAIN LINE REQUIRED -



1490 - 1890 Kg	120 - 140 lt/min	Ø max 25 cm
-----------------------	-------------------------	--------------------

Forestry mulcher, for bushes, branches and small trees, to cut up max. diameter of 25 cm, for BIG skid steer, with hydraulic system at high performance and high oil flow, with power from 110 HP to 160 HP.

STANDARD EQUIPMENT:

Hydraulic front hood. Stronger frame built with very high quality steel (DOMEX 700-SS355), and double counter blades. Drainless Piston motor of 64cc. Rotor type Q with fixed teeth. Single belt transmission (5). Hoses with 2,5 mt. (without quick release couplings). 3F - OSMA Valve - 1-bypass 2- antishock 3- oil flow automatic regulation. Pressure gauge for pressure control during shredder operation.

Technical information

Model	Code	Cutting wide cm. 	Exterior width cm. 	Weight kg. 	Required power HP 	Flow rate lt/min 	Pressure set bar
SS/TFF 180	830180	180	205	1490	110-150	120-140	270-300
SS/TFF 200	830200	200	225	1680	110-150	120-140	270-300
SS/TFF 220	830220	220	250	1890	110-150	120-140	270-300

Tools

<p>Fixed tooth with carbide insert for strong vegetation and trees Cod. Q Rotor - 180° reversible (2 sides)</p>	
<p>Optional: DCR rotor with steel profiles</p>	

Optional

<p>Valve Electro-hydraulic with cable into the cabin for the door cylinder control</p>	<p>Mechanical pushing frame</p>	<p>Hydraulic pushing frame</p>
<p>VM55 variable displacement hydr. Motor</p>	<p>VM80 variable displacement hydr. Motor</p>	
<p>DCR limiter rotor system available for all versions</p>		