

FORESTRY LINE

MINI SSK

MINI FORESTRY MULCHER FOR MINI-SKID STEER AND MINI-LOADERS



Forestry mulcher ideal for cutting shrubs, twigs and brambles, trees up to 15 cm high. DCR limiting rotor equipped with K-type fixed tools. It is applied to skid steer and compact loaders, and is suitable for working on uncultivated land, undergrowth and green areas in general, which require high power work.

STANDARD EQUIPMENT:

25 cc or 34cc piston hydraulic motor. Belt transmission with nr. 3 toothed belts, bearing with bronze cage, internal counter blade, rotor built with 12.5 mm tube, 5 mm Hardox 400 internal cover plate. Hardox underplate SKIDS slides 3F - OSMA valve - 1- bypass 2- antishock 3- automatic oil flow adjustment. Pushing frame as standard.

Technical information							
Model	Code	Cutting wide cm.	Exterior width cm.	Required power HP	Weight kg.	Flow rate It/min	Pressure set bar
MSSK 90	818090	90	108	35-50	370	50-75	200-250
MSSK 110	818110	110	128	35-50	400	50-75	200-250

Tools

Fixed tools recommended for cutting grass and dense vegetation max 12 cm. - Cod. ZPK0025 Rotor K1 33 pieces model 90 - 39 pieces model 110

Fixed tools recommended for cutting grass and dense vegetation in the presence of rocky ground max 15 cm. - Cod. ZPK0026 Rotor K2 33 pieces model 90 - 39 pieces model 110







Rotor with steel profiles (DCR) for both types of tools